







Spray guns and lances

Low and medium pressure spray guns.

<p>RB35 cone jet spray gun</p>  <p>Low pressure spray gun with variable cone jet and Stainless steel 360° swivel connection.</p> <p>Reference: 140.003 Inlet ½" F sw. Out Cone nozzle Rated Pressure 12 bar Rated Temperature 80°C Rated Flow Rate 50 Lpm. Accessory type ●</p>	<p>Heavy duty spray head</p>  <p>Stainless steel spray adjustable spray head with plastic housing.</p> <p>Reference: 140.AKRSH02 Inlet ½" F Out Cone nozzle Rated Pressure 16 bar Rated Temperature 80°C Rated Flow Rate 150 Lpm. Accessory type ●</p>	<p>Shower head</p>  <p>Stainless steel with plastic housing shower head.</p> <p>Reference: 500101 Inlet ½" F Out Shower Rated Pressure 8 bar Rated Temperature 60°C Rated Flow Rate 50 Lpm. Accessory type ●</p>
<p>RB65 cone jet spray gun</p>  <p>Low pressure spray gun with variable cone jet and 360° swivel connection.</p> <p>Reference: 140.005 Inlet ½" F sw. Out Cone nozzle Rated Pressure 24 bar Rated Temperature 90°C Rated Flow Rate 60 Lpm. Accessory type ●</p>	<p>RB65 with ST3100 quick coupling</p>  <p>Low pressure spray gun with ST3100 quick coupling and 360° swivel connection. Nozzles not included.</p> <p>Reference: 140.022 Inlet ½" F Out ST3100 QC. Rated Pressure 24 bar Rated Temperature 90°C Rated Flow Rate 100 Lpm. Accessory type ●</p>	<p>RB65 with triple click nozzle</p>  <p>Low pressure spray gun with Stainless steel triple click nozzle and 360° swivel connection.</p> <p>Reference: 140.021 Inlet ½" F Out Triple click Rated Pressure 24 bar Rated Temperature 90°C Rated Flow Rate 100 Lpm. Accessory type ●</p>









Low and medium pressure spray guns.

<p>Isolated ball valve.</p>  <p>Stainless steel isolated ball valve. Full passage.</p> <p>Reference: 140.112 Inlet ½"F Out ½"F Rated Pressure 60 bar Rated Temperature 90°C Rated Flow Rate 100 Lpm. Accessory type ●</p>	<p>Isolated ball valve with ST3100 quick coupling.</p>  <p>Stainless steel isolated ball valve. Full passage. With nozzle adapter. Nozzles not included.</p> <p>Reference: 140.114 Inlet ½"F Out ST3100 QC. Rated Pressure 60 bar Rated Temperature 90°C Rated Flow Rate 100 Lpm. Accessory type ●</p>	<p>Isolated ball valve with triple click nozzle.</p>  <p>Low pressure spray gun with Stainless steel triple click nozzle and 360° swivel connection.</p> <p>Reference: 140.113 Inlet ½"F Out Triple click Rated Pressure 24 bar Rated Temperature 90°C Rated Flow Rate 100 Lpm. Accessory type ●</p>
<p>ST3225 gun with progressive closing and ST3100 quick coupling</p>  <p>Stainless steel lockable gun with advantages from spray gun and ball valve. Nozzles not included.</p> <p>Reference: 203225650 Inlet ½"F Out ST3100 QC Rated Pressure 60 bar Rated Temperature 100°C Rated Flow Rate 100 Lpm. Accessory type ●</p>	<p>ST3100 spray gun with ST3100 quick coupling</p>  <p>Stainless steel spray gun progressive closing and nozzle adapter. Nozzles not included.</p> <p>Reference: 203100820 Inlet ½"F Out ST3100 QC. Rated Pressure 60 bar Rated Temperature 150°C Rated Flow Rate 100 Lpm. Accessory type ●</p>	<p>ST2720 spray gun with ST3100 quick coupling.</p>  <p>Stainless steel spray gun with LTF technology and 360° swivel connection. Nozzles not included.</p> <p>Reference: 202720550 Inlet ½"F Out ST3100 QC Rated Pressure 125 bar Rated Temperature 150°C Rated Flow Rate 80 Lpm. Accessory type ●</p>



Low pressure lances and nozzles

<p>Low pressure lances – extensions</p>  <p>Stainless steel lance extension with ST3100 nipple and quick coupling.</p> <p>Reference 400mm : 30.6456.40X Reference 800mm 30.6456.80X Inlet ST3100 nipple Out ST3100 QC</p> <p>Rated Pressure 100 bar Rated Temperature 150°C Accessory type ●</p>	<p>Foam lance</p>  <p>Stainless steel foam lance with ST3100 nipple and foam nozzle 50/200.</p> <p>Reference: 203100630</p> <p>Inlet ST3100 Out Nozzle 50/200</p> <p>Rated Pressure 150 bar Rated Temperature 150°C Accessory type ●</p>	<p>Triple click XL</p>  <p>Stainless steel short lance with triple click nozzle and ST3100 nipple</p> <p>Reference: 140.145XL</p> <p>Inlet ST3100 Out Triple click</p> <p>Rated Pressure 150 bar Rated Temperature 100°C Accessory type ●</p>
<p>Triple click nozzle</p>  <p>By easily turning the head there are 3 nozzles selectable. Foam, rinse, disinfect for food industry.</p> <p>Reference: 140.145 Inlet ½" M BSP Out 50°150 15°30 25°50</p> <p>Rated Pressure 150 bar Rated Temperature 150°C Accessory type ●</p>	<p>Foam lance</p>  <p>By easily turning the head there are 2 nozzles selectable ¼" NPT and 1 prefixed Foam nozzle.</p> <p>Reference: 140.148 Inlet ½" M BSP Out 50°150 ¼" F NPT ¼" F NPT</p> <p>Rated Pressure 150 bar Rated Temperature 150°C Accessory type ●</p>	<p>Nozzles with ST3100 nipple</p>  <p>Stainless steel interchangeable nozzles for food industry. Foam, Disinfect and rinse.</p> <p>Colour/ Nozzle Type Reference White 50/200 140.155 Yellow 25/50 140.160 Bleu 15/30 140.165</p> <p>Stainless steel holder 140.655 Rated Temperature 100°C Accessory type ●</p>



Low pressure lances and nozzles

High flow POM lance with valve	Chemical spray lance	Gun for liquid transfer
		
Stainless steel Ball valve with POM high flow foam lance. Perfect in combination with Foamatron	Stainless steel lance with Spray gun equipped with AISI316 ball resistant to chemicals.	Liquid transfer gun with trigger lock. PA, stainless steel and Viton seal.
Reference : 140.184	Reference: 200510550	Reference: 140.090
Inlet ¾" F BSP	Inlet ½" F BSP	Inlet 1" swivel
Foam nozzle 50/350	Out Nozzle	Rated flow 90 liter
Rated Pressure 10 bar	Rated Pressure 25 bar	Rated Pressure 5 bar
Rated Temperature 40°C	Rated Temperature 50°C	Rated Temperature 60°C
Accessory type ●	Accessory type ●	Accessory type ●





High pressure spray guns.

ST2700 Spray gun		ST2700 with ST3100 quick coupling		ST2720 with KW quick coupling	
					
Stainless steel high pressure spray gun with LTF technology.		Stainless steel high pressure spray gun with LTF technology. Equipped with ST3100 QC and 360° swivel.		Stainless steel high pressure spray gun with LTF technology. Equipped with KW QC and 360° swivel.	
Reference:	202700500	Reference:		Reference:	140.021
Inlet	3/8" F	Inlet	3/8" F swivel	Inlet	3/8" F swivel
Out	1/4" F	Out	ST3100 QC.	Out	KW QC
Rated Pressure	310 bar	Rated Pressure	310 bar	Rated Pressure	310 bar
Rated Temperature	150°C	Rated Temperature	150°C	Rated Temperature	150°C
Rated Flow Rate	45 Lpm.	Rated Flow Rate	45 Lpm.	Rated Flow Rate	45 Lpm.
Accessory type	●	Accessory type	●	Accessory type	●

High pressure Lances

Bleu stainless steel lance with dynamic foam nozzle, suitable for all Click & clean HPJET systems. Equipped with integrated air injector it creates foam without the need of compressed air							
							
Reference	Materials	Length mm	Inlet	Out	Max. press.	Max. temp	Accessoir type
200075572X	St. steel	600	KW nipple	Foam nozzle	250bar	150°C	●

Black heatproof lance with KW nipple and nozzle protector. Pressure nozzles available from 20 – 400 bar – mainly used in food industry as high pressure rinse lance for outside cleaning applications under high pressure 200bar.							
							
Reference	Materials	Length mm	Inlet	Out	Max. press.	Max. temp	Accessoir type
200028309x	St. steel	900	KW nipple	1/4" F NPT	400bar	150°C	●



Green heatproof lance with KW nipple and nozzle protector. Pressure nozzles available from 20 – 400 bar – mainly used in food industry as 40 bar rinse lance in combination with Click & clean HPJET units.



Reference	Materials	Length mm	Inlet	Out	Max. press	Max. temp	Accessoir type
200029317x	St. steel	900	KW nipple	¼" F NPT	400bar	150°C	●

Bleu heatproof lance with KW nipple and nozzle protector. Pressure nozzles available from 20 – 400 bar – mainly used in food industry as 20 bar rinse lance in combination with Click & clean HPJET units.



Reference	Materials	Length mm	Inlet	Out	Max. press	Max. temp	Accessoir type
200029315x	St. steel	900	KW nipple	¼" F NPT	400bar	150°C	●

Red heatproof lance with KW nipple and nozzle protector. Pressure nozzles available from 20 – 400 bar – mainly used in food industry as 80 bar rinse lance in combination with Click & clean HPJET units.



Reference	Materials	Length mm	Inlet	Out	Max. press	Max. temp	Accessoir type
200029318x	St. steel	900	KW nipple	¼" F NPT	400bar	150°C	●

Yellow heatproof lance with KW nipple and nozzle protector. Pressure nozzles available from 20 – 400 bar – mainly used in food industry as 5bar non foaming spray disinfection lance in combination with Click & clean HPJET units.



Reference	Materials	Length mm	Inlet	Out	Max. press.	Max. temp	Accessoir type
200029316x	St. steel	900	KW nipple	¼" F NPT	400bar	150°C	●

Black turbo heatproof lance with KW nipple and turbo rotating nozzle.



Reference	Materials	Length mm	Inlet	Out	Max. press.	Max. temp	Accessoir type
200029309x	St. steel	900	KW nipple	¼" F NPT	400bar	150°C	●

Push & pull heatproof lance with KW nipple and nozzle protector. Pressure nozzles available from 20 – 400 bar



Reference	Materials	Length mm	Inlet	Out	Max. press.	Max. temp	Accessoir type
200085610	St. steel	900	KW nipple	¼" F NPT	400bar	150°C	●