



Quick couplings

ST246 quick couplings and plugs suitable with Snap-tite couplings			
Max. 350bar / 100°C			
	Stainless steel. F thread.	Stainless steel nipple hardened. F thread.	Stainless steel nipple hardened M thread.

Thread	DN	Reference	Reference	Reference
1/4	6		040 005 423	
3/8	8,5	710 246 238 000	710 246 138 001	
1/2	11	710 246 412 000	710 246 312 001	710 246 312 101
M22	6			040 005 424

ST3100 quick couplings and plugs				
Max.250bar / 150°C				
	St. steel with isolation. F thread.	St. steel with isolation. M thread.	St. steel. F thread.	St. steel. M thread.

Thread	DN	Reference	Reference	Reference	Reference
1/4	10			040005665	
3/8	12	203100456	203100475	040005667	040005668
1/2	12	203100455	203100656	040005661	040005662

KW bayonet quick couplings an plugs			M22 quick screw couplings and plugs			
						
Coupling KW 1/4\"M st.st.	Plug KW 1/4F	Plug KW 1/4M	M22 : M. St. steel. Max. 500 bar	M22 : F. St. steel. Max. 500 bar	M22 M : F. St. steel. Max. 500 bar	M22 M : M. St. steel. Max. 500 bar

Reference	Reference	Reference	Reference	Reference	Reference	Reference
202700355	040001255	040001256	1/4 561 49	1/4 561 39	1/4 565 29	1/4 565 39
			3/8 561 69	3/8 561 59	3/8 565 49	3/8 565 59
						1/2 565 69



Stainless steel mounting parts.

Check valve 1/4" MM		Check valve 1/4" FF		Check valve 3/8" FF		Check valve 1/2" FF	
							
Opening pressure 0.05-01 bar. Max. 400bar/90°C EPDM Seal		Opening pressure 0.05-01 bar. Max. 400bar/90°C EPDM Seal		Opening pressure 0.05-01 bar. Max. 400bar/90°C EPDM Seal		Opening pressure 0.05-01 bar. Max. 400bar/90°C EPDM Seal	
Ref.	200264700	Ref.	200264500	Ref.	200264520	Ref.	200264541

Chemical Check valve 1/2" FF		Inline filter 50 micron 1/2" FF		1/2 "F BSP 60° weld swivel		1/2" BSP 60° weld nipple	
							
AISI316 With chemical resistant PTFE seal. Max. 55bar/150°C		AISI316 Stainless steel 0.5mesh replaceable filter housing. Max. 55bar/150°C		AISI316 Stainless steel Weld swivel Ø18mm – ½" hydraulic swivel		AISI316 Stainless steel weld nipple Ø21,5 – G1/2" BSP 60°	
Ref.	A-YCVG12-8I	Ref.	DAG112-8I 50M	Ref.	DKR12G12D18	Ref.	629G12D215

Installation pipes for satellites.

Equipped with 1/2"swivel connection, chemical resistant check valve, lance and colored ball valve according the passing media.

Water supply	Air supply	Premixed Foam cleaner	Premixed disinfection	Premixed acid cleaning	Out to hose reel
					
Reference: 100.280B	Reference: 100.280W	Reference: 100.280G	Reference: 100.280Y	Reference: 100.280R	Reference: 100.281